# HTG 075-20 LL

**Fire resistant cabinet for hazardous substances, type 90**



## Prime parameters

### Size of the safe

External dimensions: 1935 mm × 595 mm × 598 mm

### Colour

Choose your safe's standard colour or modify it

### Key lock

Key lock

# Technical details

| | |
|---|---|
| External dimensions (H x W x D) | 1935 mm × 595 mm × 598 mm |
| Internal dimensions (H x W x D) | 1700 mm × 492 mm × 430 mm |
| Weight | 306 kg |
| Capacity | 360 |
| Standard lock | Key lock |
| Size of the safe | Big |
| Article number | HTG 075-20 LL |
| Fire resistance | 90 minutes acc. to EN 14470-1 type F90 + TRbF 20-L |
| Tank bottoms | 3 |
| Load capacity of shelves | 75 kg |
| Lower tub | 1 |
| Perforated plate insert | 1 |
| Door opening direction | right side |
| Door opening angle | 90° |
| Lacquer/Colour | light grey (similar to RAL 7035), door – daffodil yellow RAL 1007 |
| Lock | cylindric |
| More data on the body | insulation according to German standard DIN 4102, external powder-coated housing, the internal corpus made of high-pressure laminate panels |
| More data on the door | hidden in the body, equipped with lock, a device to stop the door in the open position and a thermomechanically operated door closer (activated in case of fire) |
| Equipment | - 3 tank bottoms adjustable in height every 64 mm, with perforation in the middle, secured against tilting, - fluid-collecting bottom tray with a volume of 22 litres and perforated sheet metal cover, - earthing to avoid the risk of ignition by electrostatic charge, - socle for easy pallet truck transport, - adjustable feet for easy leveling and alignment, - ventilation from the top of the cabinet (exhaust air connection with nominal diameter 75), - extraction in the floor area, - release of supply and exhaust air closure via thermal sensor |