HTG 086-01

Fire resistant cabinet for hazardous materials ((double leaf), type 30



Prime parameters

Size of the safe

External dimensions: 1960 mm × 1195 mm × 595 mm

Resistance class and insurance

Security class D-II according to EN 1143-2

Colour

Choose your safe's standard colour or modify it

Key lock

Key lock

Technical details

External dimensions (H x W x D)	1960 mm × 1195 mm × 595 mm
Internal dimensions (H x W x D)	1600 mm × 1075 mm × 515 mm
Weight	226 kg
Capacity	886
Security class	D-II
Standard lock	Key lock
Size of the safe	Big
Article number	HTG 086-01
Fire resistance	30 minutes acc. to EN 14470-1 type F30 + TRbF 20-L
Tank bottoms	3
Load capacity of shelves	75 kg
Lower tub	1
Perforated plate insert	1
Door opening direction	both sides
Door opening angle	90°
Lacquer/Colour	light grey (similar to RAL 7035), micro pearl
Lock	cylindric
More data on the body	surface with high chemical resistance, stainless steel finish
More data on the door	double leaf, hidden in the body, equipped with lock and hydraulic shock absorbing door closer with opening lock (activated in case of fire)
Equipment	- 3 tank bottoms adjustable in height every 32 mm, with perforation in the middle, secured against tilting, - earthing to avoid the risk of ignition by electrostatic charge, - socle for easy pallet truck transport, - adjustable feet for easy leveling and alignment, - ventilation from the top of the cabinet (exhaust air connection with nominal diameter 100), - extraction in the floor area, - release of supply and exhaust air closure via thermal sensor