

HTG 087-02

Fire resistant cabinet for hazardous materials ((double leaf), type 30



Prime parameters

Size of the safe

External dimensions: 635 mm × 1100 mm × 550 mm

Colour

Choose your safe's standard colour or modify it

Key lock

Key lock

Technical details

External dimensions (H x W x D)	635 mm x 1100 mm x 550 mm
Internal dimensions (H x W x D)	375 mm x 980 mm x 472 mm
Weight	90 kg
Capacity	173
Standard lock	Key lock
Size of the safe	Medium
Article number	HTG 087-02
Fire resistance	30 minutes acc. to EN 14470-1 type F30 + TRbF 20-L
Tank bottoms	--
Lower tub	1
Perforated plate insert	1
Door opening direction	both sides
Door opening angle	90°
Lacquer/Colour	light grey (similar to RAL 7035), micro pearl
Lock	cylindric
More data on the body	surface with high chemical resistance, stainless steel finish
More data on the door	double leaf, hidden in the body, equipped with lock and hydraulic shock absorbing door closer with opening lock (activated in case of fire)
Equipment	- lower tub, perforated plate insert, - earthing to avoid the risk of ignition by electrostatic charge, - socle for easy pallet truck transport, - adjustable feet for easy leveling and alignment, - ventilation from the top of the cabinet (exhaust air connection with nominal diameter 100), - extraction in the floor area, - release of supply and exhaust air closure via thermal sensor