

HTG 088-01 Li

Fireproof battery cabinet, type 90



Prime parameters

Size of the safe

External dimensions: 1960 mm × 600 mm × 595 mm

Colour

Choose your safe's standard colour or modify it

Key lock

Key lock

Technical details

External dimensions (H x W x D)	1960 mm x 600 mm x 595 mm
Internal dimensions (H x W x D)	1600 mm x 520 mm x 480 mm
Weight	340 kg
Capacity	399
Standard lock	Key lock
Size of the safe	Big
Article number	HTG 088-01 Li
Fire resistance	90 minutes acc. to EN 14470-1 type F90 + TRbF 20-L
Tank bottoms	3
Load capacity of shelves	75 kg
Lower tub	1
Perforated plate insert	1
Door opening direction	right side
Door opening angle	90°
Lacquer/Colour	light grey (similar to RAL 7035), micro pearl, edges distinguished by colour
Lock	cylindric
More data on the body	material with surface coating A2 – non-flammable; homogeneous, solid, moisture-insensitive and non-absorbent material (single-layer structure)
More data on the door	hidden in the body, equipped with lock and hydraulic shock absorbing door closer with opening lock (activated in case of fire)
Equipment	- resistance to fire from the inside and the outside, - earthing to avoid the risk of ignition by electrostatic charge, - protection against unauthorised access - up and down door locking - 4 bath shelves adjustable in height every 32 mm, with perforation in the middle, secured against tilting, - seals to hermetically seal the enclosure during a fire, - cable entry from the top of the enclosure, - 100 mm high base for easy pallet truck transport 100 mm high base for easy transport with a pallet truck, - adjustable feet for easy leveling and alignment, - integrated ventilation system in the rear wall, smoke detector and fan as standard (exhaust air connection with nominal diameter 100), - cold smoke detection, - extraction in the floor area, - release of supply and exhaust air closure via thermal sensor