

HTG 089-01

Fire resistant cabinet for hazardous materials (double leaf), type 90



Prime parameters

Size of the safe

External dimensions: 1960 mm × 1200 mm × 595 mm

Colour

Choose your safe's standard colour or modify it

Key lock

Key lock

Technical details

| | |
|---------------------------------|--|
| External dimensions (H x W x D) | 1960 mm x 1200 mm x 595 mm |
| Internal dimensions (H x W x D) | 1603 mm x 1116 mm x 483 mm |
| Weight | 600 kg |
| Capacity | 864 |
| Standard lock | Key lock |
| Size of the safe | Big |
| Article number | HTG 089-01 |
| Fire resistance | 90 minutes acc. to EN 14470-1 type F90 + TRbF 20-L |
| Tank bottoms | 3 |
| Load capacity of shelves | 75 kg |
| Lower tub | 1 |
| Perforated plate insert | 1 |
| Door opening direction | both sides |
| Door opening angle | 90° |
| Lacquer/Colour | light grey (similar to RAL 7035), micro pearl, edges distinguished by colour |
| Lock | cylindric |
| More data on the body | material with surface coating A2 – non-flammable; homogeneous, solid, moisture-insensitive and non-absorbent material (single-layer structure) |
| More data on the door | double leaf, hidden in the body, equipped with lock and hydraulic shock absorbing door closer with opening lock (activated in case of fire) |
| Equipment | - 3 tank bottoms adjustable in height every 32 mm, with perforation in the middle, secured against tilting, - earthing to avoid the risk of ignition by electrostatic charge, - socle for easy pallet truck transport, - adjustable feet for easy leveling and alignment, - ventilation from the top of the cabinet (exhaust air connection with nominal diameter 100), - extraction in the floor area, - release of supply and exhaust air closure via thermal sensor |