HTG 089-01 Li

Fireproof battery cabinet (double leaf), type 90



Prime parameters

Size of the safe

External dimensions: 1960 mm × 1200 mm × 595 mm

Colour

Choose your safe's standard colour or modify it

Key lock

Key lock

Technical details

External dimensions (H x W x D)	1960 mm × 1200 mm × 595 mm
Internal dimensions (H x W x D)	1603 mm × 1116 mm × 483 mm
Weight	600 kg
Capacity	864
Standard lock	Key lock
Size of the safe	Big
Article number	HTG 089-01 Li
Fire resistance	90 minutes acc. to EN 14470-1 type F90 + TRbF 20-L
Tank bottoms	3
Load capacity of shelves	75 kg
Lower tub	1
Perforated plate insert	1
Door opening direction	both sides
Door opening angle	90°
Lacquer/Colour	light grey (similar to RAL 7035), micro pearl, edges distinguished by colour
Lock	cylindric
More data on the body	material with surface coating A2 – non-flammable; homogeneous, solid, moisture-insensitive and non-absorbent material (single-layer structure)
More data on the door	double leaf, hidden in the body, equipped with lock and hydraulic shock absorbing door closer with opening lock (activated in case of fire)
Equipment	- resistance to fire from the inside and the outside, - earthing to avoid the risk of ignition by electrostatic charge, - protection against unauthorised access - up and down door locking - 4 bath shelves adjustable in height every 32 mm, with perforation in the middle, secured against tilting, - seals to hermetically seal the enclosure during a fire, - cable entry from the top of the enclosure, - 100 mm high base for easy pallet truck transport 100 mm high base for easy transport with a pallet truck, - adjustable feet for easy leveling and alignment, - integrated ventilation system in the rear wall, smoke detector and fan as standard (exhaust air connection with nominal diameter 100), - cold smoke detection, - extraction in the floor area, - release of supply and exhaust air closure via thermal sensor