# HTG 090-01

**Fire resistant cabinet for hazardous materials (double leaf), type 90**



## Prime parameters

### Size of the safe

External dimensions: 661 mm × 1100 mm × 500 mm

### Colour

Choose your safe's standard colour or modify it

### Key lock

Key lock

# Technical details

| | |
|---|---|
| External dimensions (H x W x D) | 661 mm × 1100 mm × 500 mm |
| Internal dimensions (H x W x D) | 491 mm × 1016 mm × 355 mm |
| Weight | 223 kg |
| Capacity | 177 |
| Standard lock | Key lock |
| Size of the safe | Medium |
| Article number | HTG 090-01 |
| Fire resistance | 90 minutes acc. to EN 14470-1 type F90 + TRbF 20-L |
| Tank bottoms | 1 |
| Load capacity of shelves | 75 kg |
| Lower tub | 1 |
| Perforated plate insert | 1 |
| Door opening direction | both sides |
| Door opening angle | 90° |
| Lacquer/Colour | light grey (similar to RAL 7035), micro pearl, edges distinguished by colour |
| Lock | cylindric |
| More data on the body | material with surface coating A2 – non-flammable; homogeneous, solid, moisture-insensitive and non-absorbent material (single-layer structure) |
| More data on the door | double leaf, hidden in the body, equipped with lock and hydraulic shock absorbing door closer with opening lock (activated in case of fire) |
| Equipment | - lower tub, perforated plate insert, - earthing to avoid the risk of ignition by electrostatic charge, - socle for easy pallet truck transport, - adjustable feet for easy leveling and alignment, - ventilation from the top of the cabinet, (exhaust air connection with nominal diameter 100), - extraction in the floor area, - release of supply and exhaust air closure via thermal sensor |