HTG 091-01 Li Basic

Fireproof lithium battery cabinet (double leaf), type 90



Prime parameters

Size of the safe

External dimensions: 2048 mm × 1148 mm × 591 mm

Colour

Choose your safe's standard colour or modify it

Key lock

Key lock

Technical details

External dimensions (H x W x D)	2048 mm × 1148 mm × 591 mm
Internal dimensions (H x W x D)	1804 mm × 1004 mm × 440 mm
Weight	650 kg
Standard lock	Key lock
Size of the safe	Big
Article number	HTG 091-01 Li Basic
Fire resistance	90 minutes acc. to EN 1363-1 from outside and inside
Tank bottoms	4 grid, adjustable
Load capacity of shelves	75 kg
Door opening direction	both sides
Door opening angle	180°
Lacquer/Colour	light grey (similar to RAL 7035), individual colour possible
Lock	cylindric
More data on the body	housing made of noncombustible material in class A2 – s1, d0, with decorative surface, of high mechanical resistance
More data on the door	- two-leaf type, - integrated into the body, - opening and closing smoothly, moving freely, - equipped with a lock
Equipment	- tested fire load insulation, - a perimeter fire seal that self-inflates in the event of a fire, - protection against unauthorised access – pivot lever with double-bit key lock, - a cold-smoke-tight locking system, - top and bottom cable entry, - integrated ventilation system at the back wall: smoke detector and fan, - accessible plinth (e.g. fork-lift forks), height 100 mm, with a removable cover, - wall anchorage possible, - safety cabinet with active fire suppression – can stop the spread of fire inside and minimise the escape of toxic fumes. Optional equipment (at extra cost): grid shelves
Adapted for wall anchoring	yes