

D 111-05

Burglar- and fire-proof safe



Prime parameters

Size of the safe

External dimensions: 1343 mm × 710 mm × 497 mm

Resistance class and insurance

Security class II according to EN 1143-1

Colour

Choose your safe's standard colour or modify it

Key lock

Key lock

Technical details

| | |
|-------------------------------------|--|
| External dimensions (H x W x D) | 1343 mm x 710 mm x 497 mm |
| Internal dimensions (H x W x D) | 1204 mm x 572 mm x 319 mm |
| Weight | 451 kg |
| Capacity | 219 l |
| Security class | II |
| Limit of protected value – home | to 100.000 € |
| Limit of protected value – company | to 50.000 € |
| Standard lock | Key lock |
| Size of the safe | Medium |
| Article number | D 111-05 |
| Adjustable shelves | 3 |
| File binders | 23 |
| Anti-burglary protection standard | EN 1143-1 |
| Certification body | VdS |
| Fire resistance | S 60 P acc. to the EN 1047-1 standard – 60 min. for paper documents |
| Door opening direction | right side |
| Door thickness | 114 mm |
| Door opening angle | 180° |
| Door clearance dimensions | 1198 x 569 mm |
| Protruding door hinges/fittings | 60 mm |
| Lock | high security key lock (2 keys) |
| Features of the lock | 3-sided bolt locking system; additional fixed pins at the hinge side |
| Lacquer/Colour | light grey RAL 7035 |
| Adapted for anchoring in the ground | yes |
| More data on the body | multi-wall 62 mm thick, with fire protection strip |
| More data on the door | armoured plate to protect the lock from drilling |