

D 111-16

Burglar- and fire-proof safe, 2-door



Prime parameters

Size of the safe

External dimensions: 1905 mm × 1252 mm × 497 mm

Resistance class and insurance

Security class II according to EN 1143-1

Colour

Choose your safe's standard colour or modify it

Key lock

Key lock

Technical details

| | |
|-------------------------------------|--|
| External dimensions (H x W x D) | 1905 mm x 1252 mm x 497 mm |
| Internal dimensions (H x W x D) | 1766 mm x 1116 mm x 309 mm |
| Weight | 989 kg |
| Capacity | 609 l |
| Security class | II |
| Limit of protected value – home | to 100.000 € |
| Limit of protected value – company | to 50.000 € |
| Standard lock | Key lock |
| Size of the safe | Big |
| Article number | D 111-16 |
| Adjustable shelves | 4 |
| File binders | 70 |
| Anti-burglary protection standard | EN 1143-1 |
| Certification body | VdS |
| Fire resistance | S 60 P acc. to the EN 1047-1 standard – 60 min. for paper documents |
| Door opening direction | both sides |
| Door thickness | 114 mm |
| Door opening angle | 180° |
| Door clearance dimensions | 1760 x 1111 mm |
| Protruding door hinges/fittings | 60 mm |
| Lock | high security key lock (2 keys) |
| Features of the lock | 3-sided bolt locking system; additional fixed pins at the hinge side |
| Lacquer/Colour | light grey RAL 7035 |
| Adapted for anchoring in the ground | yes |
| More data on the body | multi-wall 62 mm thick, with fire protection strip |
| More data on the door | double-wing, drill-resistant armoured plate in the lock area |