

HPFII 1174

Burglar- and fire-proof safe



Prime parameters

Size of the safe

External dimensions: 1137 mm × 704 mm × 471 mm

Resistance class and insurance

Security class 0 according to EN 1143-1

Colour

Choose your safe's standard colour or modify it

Key lock

Key lock

Technical details

External dimensions (H x W x D)	1137 mm x 704 mm x 471 mm
Internal dimensions (H x W x D)	1036 mm x 592 mm x 339 mm
Weight	315 kg
Capacity	207 l
Security class	0
Limit of protected value – home	to 40.000 €
Limit of protected value – company	to 10.000 €
Standard lock	Key lock
Size of the safe	Big
Article number	HPFII 1174
Adjustable shelves	3
File binders	21
Anti-burglary protection standard	EN 1143-1
Certification body	VdS
Fire resistance	S 60 P acc. to the EN 1047-1 standard – 60 min. for paper documents
Door opening direction	right side
Door thickness	95 mm
Door opening angle	180°
Door clearance dimensions	1021 x 569 mm
Protruding door hinges/fittings	60 mm
Lock	high security key lock (2 keys)
Features of the lock	locking mechanism on all sides, among this fixed pins on hinge side
Lacquer/Colour	light grey RAL 7035
Adapted for anchoring in the ground	yes
More data on the body	multi-wall 50 mm, with filling and gaskets