

HPFVI 865

Burglar- and fire-proof safe



Prime parameters

Size of the safe

External dimensions: 822 mm × 595 mm × 497 mm

Resistance class and insurance

Security class II according to EN 1143-1

Colour

Choose your safe's standard colour or modify it

Key lock

Key lock

Technical details

| | |
|-------------------------------------|---|
| External dimensions (H x W x D) | 822 mm x 595 mm x 497 mm |
| Internal dimensions (H x W x D) | 683 mm x 457 mm x 319 mm |
| Weight | 280 kg |
| Capacity | 99 l |
| Security class | II |
| Limit of protected value – home | to 100.000 € |
| Limit of protected value – company | to 50.000 € |
| Standard lock | Key lock |
| Size of the safe | Medium |
| Article number | HPFVI 865 |
| Adjustable shelves | 2 |
| File binders | 12 |
| Anti-burglary protection standard | EN 1143-1 |
| Certification body | VdS |
| Fire resistance | S 60 P acc. to the EN 1047-1 standard – 60 min. for paper documents |
| Door opening direction | right side |
| Door thickness | 114 mm |
| Door opening angle | 180° |
| Door clearance dimensions | 677 x 454 mm |
| Protruding door hinges/fittings | 60 mm |
| Lock | high security key lock (2 keys) |
| Features of the lock | 4-sided bolt locking system, among this fixed pins on hinge side |
| Lacquer/Colour | light grey RAL 7035 |
| Adapted for anchoring in the ground | yes |
| More data on the body | multi-wall, with filling and gaskets |
| More data on the door | armoured plate to protect the lock from drilling |