HPFVI 1584

Burglar- and fire-proof safe



Prime parameters

Size of the safe

External dimensions: 1589 mm × 892 mm × 497 mm

Resistance class and insurance

Security class II according to EN 1143-1

Colour

Choose your safe's standard colour or modify it

Key lock

Key lock

Technical details

External dimensions (H x W x D)	1589 mm × 892 mm × 497 mm
Internal dimensions (H x W x D)	1450 mm × 756 mm × 319 mm
Weight	609 kg
Capacity	349 l
Security class	II
Limit of protected value – home	to 100.000 €
Limit of protected value – company	to 50.000 €
Standard lock	Key lock
Size of the safe	Big
Article number	HPFVI 1584
Adjustable shelves	3
File binders	40
Anti-burglary protection standard	EN 1143-1
Certification body	VdS
Fire resistance	S 60 P acc. to the EN 1047-1 standard – 60 min. for paper documents
Door opening direction	right side
Door thickness	114 mm
Door opening angle	180°
Door clearance dimensions	1444 x 751 mm
Protruding door hinges/fittings	60 mm
Lock	high security key lock (2 keys)
Features of the lock	4-sided bolt locking system, among this fixed pins on hinge side
Lacquer/Colour	light grey RAL 7035
Adapted for anchoring in the ground	yes
More data on the body	multi-wall, with filling and gaskets
More data on the door	armoured plate to protect the lock from drilling