HPFVII 1065

Burglar- and fire-proof safe



Prime parameters

Size of the safe
External dimensions: 1068 mm × 619 mm × 565 mm

Resistance class and insurance
Security class II according to EN 1143-1

Colour
Choose your safe's standard colour or modify it

Key lock
Key lock

Technical details

External dimensions (H x W x D)	1068 mm × 619 mm × 565 mm
Internal dimensions (H x W x D)	769 mm × 435 mm × 352 mm
Weight	389 kg
Capacity	117 l
Security class	II
Limit of protected value – home	to 100.000 €
Limit of protected value – company	to 50.000 €
Standard lock	Key lock
Size of the safe	Big
Article number	HPFVII 1065
Adjustable shelves	2
File binders	10
Anti-burglary protection standard	EN 1143-1
Certification body	VdS
Fire resistance	S 120 P acc. to the EN 1047-1 standard – 120 min. for paper documents
Door opening direction	right side
Door thickness	135 mm
Door opening angle	180°
Door clearance dimensions	739 x 390 mm
Protruding door hinges/fittings	60 mm
Lock	high security key lock (2 keys)
Features of the lock	3-sided bolt locking system, fixed pins to protect the hinge area
Lacquer/Colour	light grey RAL 7035
Adapted for anchoring in the ground	yes
More data on the body	multi-wall 86 mm thick, with wrap-around fire safety strip
More data on the door	multi-walled