HPFVII 1885

Burglar- and fire-proof safe



Prime parameters

Size of the safe

External dimensions: 1811 mm × 821 mm × 573 mm

Resistance class and insurance

Security class II according to EN 1143-1

Colour

Choose your safe's standard colour or modify it

Key lock

Key lock

Technical details

External dimensions (H x W x D)	1811 mm × 821 mm × 573 mm
Internal dimensions (H x W x D)	1503 mm × 637 mm × 350 mm
Weight	774 kg
Capacity	334 l
Security class	II
Limit of protected value – home	to 100.000 €
Limit of protected value – company	to 50.000 €
Standard lock	Key lock
Size of the safe	Big
Article number	HPFVII 1885
Adjustable shelves	3
File binders	32
Anti-burglary protection standard	EN 1143-1
Certification body	VdS
Fire resistance	S 120 P acc. to the EN 1047-1 standard – 120 min. for paper documents
Door opening direction	right side
Door thickness	135 mm
Door opening angle	180°
Door clearance dimensions	1465 x 574 mm
Protruding door hinges/fittings	60 mm
Lock	high security key lock (2 keys)
Features of the lock	3-sided bolt locking system, fixed pins to protect the hinge area
Lacquer/Colour	light grey RAL 7035
Adapted for anchoring in the ground	yes
More data on the body	multi-wall 86 mm thick, with wrap-around fire safety strip
More data on the door	multi-walled