

HPFVII 1885

Burglar- and fire-proof safe



Prime parameters

Size of the safe

External dimensions: 1811 mm × 821 mm × 573 mm

Resistance class and insurance

Security class II according to EN 1143-1

Colour

Choose your safe's standard colour or modify it

Key lock

Key lock

Technical details

| | |
|-------------------------------------|---|
| External dimensions (H x W x D) | 1811 mm x 821 mm x 573 mm |
| Internal dimensions (H x W x D) | 1503 mm x 637 mm x 350 mm |
| Weight | 774 kg |
| Capacity | 334 l |
| Security class | II |
| Limit of protected value – home | to 100.000 € |
| Limit of protected value – company | to 50.000 € |
| Standard lock | Key lock |
| Size of the safe | Big |
| Article number | HPFVII 1885 |
| Adjustable shelves | 3 |
| File binders | 32 |
| Anti-burglary protection standard | EN 1143-1 |
| Certification body | VdS |
| Fire resistance | S 120 P acc. to the EN 1047-1 standard – 120 min. for paper documents |
| Door opening direction | right side |
| Door thickness | 135 mm |
| Door opening angle | 180° |
| Door clearance dimensions | 1465 x 574 mm |
| Protruding door hinges/fittings | 60 mm |
| Lock | high security key lock (2 keys) |
| Features of the lock | 3-sided bolt locking system, fixed pins to protect the hinge area |
| Lacquer/Colour | light grey RAL 7035 |
| Adapted for anchoring in the ground | yes |
| More data on the body | multi-wall 86 mm thick, with wrap-around fire safety strip |
| More data on the door | multi-walled |