# HPKTF 300-06

Fireproof safe for office



## Prime parameters

### Size of the safe

External dimensions: 1170 mm × 700 mm × 510 mm

### Resistance class and insurance

Security class S1 according to EN 14450

### Colour

Choose your safe's standard colour or modify it

### Key lock

Key lock

# Technical details

| | |
|---|---|
| External dimensions (H x W x D) | 1170 mm × 700 mm × 510 mm |
| Internal dimensions (H x W x D) | 1029 mm × 565 mm × 348 mm |
| Weight | 129 kg |
| Capacity | 202 l |
| Security class | S1 |
| Limit of protected value – home | to 5.000 € |
| Limit of protected value – company | to 2.500 € |
| Standard lock | Key lock |
| Size of the safe | Big |
| Article number | HPKTF 300-06 |
| Adjustable shelves | 2 |
| File binders | 21 |
| Anti-burglary protection standard | EN 14450 |
| Fire resistance | LFS 30 P acc. to the EN 15659 standard – 30 min. for paper documents |
| Door opening direction | right side |
| Door thickness | 78 mm |
| Door opening angle | 180° |
| Door clearance dimensions | 1029 x 534 mm |
| Protruding door hinges/fittings | 60 mm |
| Lock | high security key lock (2 keys) |
| Features of the lock | 3-sided bolt locking system; in addition, fixed pins to protect the hinge area |
| Lacquer/Colour | light grey RAL 7035 |
| Adapted for anchoring in the ground | yes |
| More data on the body | double-walled, 63 mm thick |