

## HPKTF 300-08

Fireproof safe for office



### Prime parameters

#### Size of the safe

External dimensions: 1870 mm × 700 mm × 510 mm

#### Resistance class and insurance

Security class S1 according to EN 14450

#### Colour

Choose your safe's standard colour or modify it

#### Key lock

Key lock

# Technical details

External dimensions (H x W x D)	1870 mm x 700 mm x 510 mm
Internal dimensions (H x W x D)	1729 mm x 565 mm x 348 mm
Weight	188 kg
Capacity	340 l
Security class	S1
Limit of protected value – home	to 5.000 €
Limit of protected value – company	to 2.500 €
Standard lock	Key lock
Size of the safe	Big
Article number	HPKTF 300-08
Adjustable shelves	4
File binders	35
Anti-burglary protection standard	EN 14450
Fire resistance	LFS 30 P acc. to the EN 15659 standard – 30 min. for paper documents
Door opening direction	right side
Door thickness	78 mm
Door opening angle	180°
Door clearance dimensions	1729 x 534 mm
Protruding door hinges/ fittings	60 mm
Lock	high security key lock (2 keys)
Features of the lock	3-sided bolt locking system; in addition, fixed pins to protect the hinge area
Lacquer/Colour	light grey RAL 7035
Adapted for anchoring in the ground	yes
More data on the body	double-walled, 63 mm thick