HPKTF 300-11

Fireproof safe for office, 2-door

Prime parameters

Size of the safe

External dimensions: 1870 mm × 1300 mm × 510 mm

Resistance class and insurance

Security class S1 according to EN 14450

Colour

Choose your safe's standard colour or modify it

Key lock

Key lock

Technical details

External dimensions (H x W x D)	1870 mm × 1300 mm × 510 mm
Internal dimensions (H x W x D)	1729 mm × 1165 mm × 348 mm
Weight	298 kg
Capacity	701 l
Security class	S1
Limit of protected value – home	to 5.000 €
Limit of protected value – company	to 2.500 €
Standard lock	Key lock
Size of the safe	Big
Article number	HPKTF 300-11
Adjustable shelves	4
File binders	75
Anti-burglary protection standard	EN 14450
Fire resistance	LFS 30 P acc. to the EN 15659 standard – 30 min. for paper documents
Door opening direction	both sides
Door thickness	78 mm
Door opening angle	180°
Door clearance dimensions	1729 x 1134 mm
Protruding door hinges/fittings	60 mm
Lock	high security key lock (2 keys)
Features of the lock	3-sided bolt locking system; in addition, fixed pins to protect the hinge area
Lacquer/Colour	light grey RAL 7035
Adapted for anchoring in the ground	yes
More data on the body	double-walled, 63 mm thick
More data on the door	double-wing