

## HPKTF 400-08

Fireproof safe for office



### Prime parameters

#### Size of the safe

External dimensions: 1875 mm × 705 mm × 527 mm

#### Resistance class and insurance

Security class S2 according to EN 14450

#### Colour

Choose your safe's standard colour or modify it

#### Key lock

Key lock

# Technical details

External dimensions (H x W x D)	1875 mm x 705 mm x 527 mm
Internal dimensions (H x W x D)	1729 mm x 565 mm x 348 mm
Weight	268 kg
Capacity	339 l
Security class	S2
Limit of protected value – home	to 30.000 €
Limit of protected value – company	to 2.500 €
Standard lock	Key lock
Size of the safe	Big
Article number	HPKTF 400-08
Adjustable shelves	4
File binders	35
Anti-burglary protection standard	EN 14450
Fire resistance	LFS 30 P acc. to the PN-EN 15659 standard – 30 min. for paper documents
Door opening direction	right side
Door thickness	94 mm
Door opening angle	180°
Door clearance dimensions	1729 x 534 mm
Protruding door hinges/fittings	60 mm
Lock	high security key lock (2 keys)
Features of the lock	3-sided bolt locking system; in addition, fixed pins to protect the hinge area
Lacquer/Colour	light grey RAL 7035
Adapted for anchoring in the ground	yes
More data on the body	double-wall with fire insulation