HPKTF 400-10

Fireproof safe for office, 2-door



Prime parameters

Size of the safe

External dimensions: 1875 mm × 955 mm × 527 mm

Resistance class and insurance

Security class S2 according to EN 14450

Colour

Choose your safe's standard colour or modify it

Key lock

Key lock

Technical details

External dimensions (H x W x D)	1875 mm × 955 mm × 527 mm
Internal dimensions (H x W x D)	1729 mm × 815 mm × 348 mm
Weight	338 kg
Capacity	490 l
Security class	S2
Limit of protected value – home	to 30.000 €
Limit of protected value – company	to 2.500 €
Standard lock	Key lock
Size of the safe	Big
Article number	HPKTF 400-10
Adjustable shelves	4
File binders	50
Anti-burglary protection standard	EN 14450
Fire resistance	LFS 30 P acc. to the PN-EN 15659 standard – 30 min. for paper documents
Door opening direction	both sides
Door thickness	94 mm
Door opening angle	180°
Door clearance dimensions	1729 x 784 mm
Protruding door hinges/fittings	60 mm
Lock	high security key lock (2 keys)
Features of the lock	3-sided bolt locking system; in addition, fixed pins to protect the hinge area
Lacquer/Colour	light grey RAL 7035
Adapted for anchoring in the ground	yes
More data on the body	double-wall with fire insulation
More data on the door	double-wing