

HPTV 2

Armoured door



Prime parameters

Size of the safe

External dimensions: 1835 mm × 1050 mm × 240 mm

Resistance class and insurance

Security class I according to EN 1143-1

Colour

Choose your safe's standard colour or modify it

Key lock

Key lock

Technical details

External dimensions (H x W x D)	1835 mm x 1050 mm x 240 mm
Internal dimensions (H x W x D)	mm x mm x mm
Weight	250 kg
Security class	I
Limit of protected value – home	to 65.000 €
Limit of protected value – company	to 20.000 €
Standard lock	Key lock
Article number	HPTV 2
Anti-burglary protection standard	EN 1143-1
Door opening direction	right side
Certification body	VdS
Lock	high security key lock (2 keys)
Door clearance dimensions	1680 x 830 mm
Door opening angle	180°
Features of the lock	- 3-sided bolt locking system with pins of 35 mm diameter, - fixed bolts at the hinge side, - in addition, the lock is secured against drilling and the bolts against balancing
Lacquer/Colour	light grey RAL 7035
Wall opening dimensions	1800 x 1000 mm
Door thickness	125 mm
Protruding door hinges/fittings	60 mm
Door properties	- four-walled structure, - solid frame made of profiled steel, anchored to the wall, - additional reinforcements in the area of the lock and bolting system, - fire insulation