HPTV 5

Armoured door



Prime parameters

Size of the safe

External dimensions: 1795 mm × 870 mm × 240 mm

Resistance class and insurance

Security class I according to EN 1143-1

Colour

Choose your safe's standard colour or modify it

Key lock

Key lock

Technical details

External dimensions (H x W x D)	1795 mm × 870 mm × 240 mm
Internal dimensions (H x W x D)	mm × mm × mm
Weight	225 kg
Security class	I
Limit of protected value – home	to 65.000 €
Limit of protected value – company	to 20.000 €
Standard lock	Key lock
Article number	HPTV 5
Anti-burglary protection standard	EN 1143-1
Fire resistance	LFS 30 P - 30 min. for paper documents acc. to PN-EN 15659
Door opening direction	right side
Certification body	VdS
Lock	high security key lock (2 keys)
Door clearance dimensions	1685 x 710 mm
Door opening angle	180°
Features of the lock	- 3-sided bolt locking system with pins of 35 mm diameter, - in addition, the lock is secured against drilling and the bolts against balancing
Lacquer/Colour	light grey RAL 7035
Wall opening dimensions	1800 x 880 mm
Door thickness	125 mm
Protruding door hinges/fittings	60 mm
Door properties	- four-walled structure, - solid steel frame, - increased fire resistance in accordance with DIN 4102