

HRS 46006

Burglar- and fire-proof safe



Prime parameters

Size of the safe

External dimensions: 1800 mm × 1350 mm × 560 mm

Resistance class and insurance

Security class I according to EN 1143-1

Colour

Choose your safe's standard colour or modify it

Key lock

Key lock

Technical details

External dimensions (H x W x D)	1800 mm x 1350 mm x 560 mm
Internal dimensions (H x W x D)	1505 mm x 1193 mm x 358 mm
Weight	1025 kg
Capacity	642 l
Security class	I
Limit of protected value – home	to 65.000 €
Limit of protected value – company	to 20.000 €
Standard lock	Key lock
Size of the safe	Big
Article number	HRS 46006
Adjustable shelves	3
File binders	67
Anti-burglary protection standard	EN 1143-1
Certification body	VdS
Fire resistance	S 120 P acc. to the EN 1047-1 standard – 120 min. for paper documents
Door opening direction	both sides
Door thickness	132 mm
Door opening angle	180°
Door clearance dimensions	1453 x 1103 mm
Protruding door hinges/fittings	60 mm
Lock	high security key lock (2 keys)
Features of the lock	4-sided bolt locking system
Lacquer/Colour	light grey RAL 7035
Adapted for anchoring in the ground	yes
More data on the body	multi-wall, 72 mm thick