

HTAA 100-13

Service transfer safe



Prime parameters

Size of the safe

External dimensions: 1408 mm × 500 mm × 700 mm

Colour

Choose your safe's standard colour or modify it

Key lock

Key lock

Technical details

External dimensions (H x W x D)	1408 mm x 500 mm x 700 mm
Internal dimensions (H x W x D)	564 mm x 494 mm x 276 mm
Weight	190 kg
Capacity	76 l
Standard lock	Key lock
Size of the safe	Big
Article number	HTAA 100-13
Drop system	hatch
Lock against deposit catching	no
Anti-burglary protection standard	EN 14450
Door opening angle	90°
Door opening direction	right side
Door thickness	53 mm
Door clearance dimensions	1344 x 392 mm
Lacquer/Colour	light grey RAL 7035
Lock	high security key lock (2 keys)
Features of the lock	3-sided bolt locking system; in addition, fixed pins on hinge side
Interior fittings	- 3 drop-off and pick-up compartments above the deposit system, fitted with an ZS 58 DT electronic lock with a weatherproof metal keypad, - all dispensing boxes and the insertion system are protected against the weather by a stainless steel door with a magnetic lock
Protruding door hinges/fittings	12 mm
Adapted for wall anchoring	yes
Adapted for anchoring in the ground	yes