HTAA 500-01

Service transfer safe



Prime parameters

Size of the safe

External dimensions: 1553 mm × 500 mm × 500 mm

Colour

Choose your safe's standard colour or modify it

Key lock

Key lock

Technical details

External dimensions (H x W x D)	1553 mm × 500 mm × 500 mm
Internal dimensions (H x W x D)	1495 mm × 390 mm × 390 mm
Weight	150 kg
Capacity	l
Standard lock	Key lock
Size of the safe	Big
Article number	HTAA 500-01
Drop system	drawer
Door thickness	3 mm
Lacquer/Colour	brushed stainless steel on all sides
More data on the body	facade installation or free-standing variant possible
Interior fittings	Construction: - modular (receiving and dispensing modules can be supplied and fitted separately), - safe made of 3 mm stainless steel, stainless steel finish Receiving module – external dimension: 900 x500 x 500 mm (H/W/D). Fittings: - A4 envelope acceptor drawer, - deposit box door, selectable from front, rear or side Dispensing module – external dimension: 600x 500x 500 mm (H/W/D). Equipment: - deposit dispensing drawer, - service door at the back, - keypad and display protected against vandalism. Electronics: - voltage 220-240 V, 50-60 Hz, - magnets 24 V, - control element - EEPROM microprocessor, - code memory function in case of power failure, - list of openings, - lock function in case of incorrect opening attempts. Number of keys or cards issued: 8, this can be increased by further 8 to 32 keys in the set.
Adapted for wall anchoring	yes
Adapted for anchoring in the ground	yes