# HTDPII 1

Drawer safe



## Prime parameters

### Size of the safe

External dimensions: 800 mm × 650 mm × 550 mm

### Resistance class and insurance

Security class D-II according to EN 1143-2

### Colour

Choose your safe's standard colour or modify it

### Key lock

Key lock

# Technical details

| | |
|---|---|
| External dimensions (H x W x D) | 800 mm × 650 mm × 550 mm |
| Internal dimensions (H x W x D) | 279 mm × 534 mm × 385 mm |
| Weight | 385 kg |
| Capacity | 57 l |
| Security class | D-II |
| Limit of protected value – home | to 50.000 € |
| Limit of protected value – company | to 50.000 € |
| Standard lock | Key lock |
| Size of the safe | Medium |
| Article number | HTDPII 1 |
| Lock against deposit catching | yes |
| Drop system | drawer |
| Adjustable shelves | 1 |
| Anti-burglary protection standard | EN 1143-2 |
| Lacquer/Colour | light grey RAL 7035, structure varnish |
| Lock | key lock in the door and the drawer |
| Door opening direction | right side |
| Door opening angle | 180° |
| Door thickness | 110 mm |
| Door clearance dimensions | 466 x 516 mm |
| Protruding door hinges/fittings | 60 mm |
| Features of the lock | - 3-sided bolt locking system, additional pins in the hinge area, - emergency bolt locking activated at an attempted break-in |
| Adapted for anchoring in the ground | yes |
| Interior fittings | - 200 mm high drawer on telescopic rails, with armouring and special concrete filling, - max. deposit dimensions: 290*400*20, 220*400*50, 90*400*80 mm |
| More data on the body | 52 mm thick, multi-walled on all sides, complete with high-strength special concrete filling |