

HTDPII 4

Drawer safe



Prime parameters

Size of the safe

External dimensions: 1400 mm × 650 mm × 550 mm

Resistance class and insurance

Security class D-II according to EN 1143-2

Colour

Choose your safe's standard colour or modify it

Key lock

Key lock

Technical details

External dimensions (H x W x D)	1400 mm x 650 mm x 550 mm
Internal dimensions (H x W x D)	879 mm x 534 mm x 385 mm
Weight	630 kg
Capacity	180 l
Security class	D-II
Limit of protected value – home	to 50.000 €
Limit of protected value – company	to 50.000 €
Standard lock	Key lock
Size of the safe	Big
Article number	HTDPII 4
Lock against deposit catching	yes
Drop system	drawer
Adjustable shelves	1
Anti-burglary protection standard	EN 1143-2
Lacquer/Colour	light grey RAL 7035, structure varnish
Lock	key lock in the door and the drawer
Door opening direction	right side
Door opening angle	180°
Door thickness	110 mm
Door clearance dimensions	1066 x 516 mm
Protruding door hinges/fittings	60 mm
Features of the lock	- 3-sided bolt locking system, additional pins in the hinge area, - emergency bolt locking activated at an attempted break-in
Adapted for anchoring in the ground	yes
Interior fittings	- 200 mm high drawer on telescopic rails, with armouring and special concrete filling, - max. deposit dimensions: 290*400*20, 220*400*50, 90*400*80 mm
More data on the body	52 mm thick, multi-walled on all sides, complete with high-strength special concrete filling