

HTDPIII 1

Drawer safe



Prime parameters

Size of the safe

External dimensions: 800 mm × 650 mm × 550 mm

Resistance class and insurance

Security class D-III according to EN 1143-2

Colour

Choose your safe's standard colour or modify it

Key lock

Key lock

Technical details

| | |
|-------------------------------------|--|
| External dimensions (H x W x D) | 800 mm x 650 mm x 550 mm |
| Internal dimensions (H x W x D) | 256 mm x 518 mm x 357 mm |
| Weight | 470 kg |
| Capacity | 47 l |
| Security class | D-III |
| Limit of protected value – home | to 100.000 € |
| Limit of protected value – company | to 100.000 € |
| Standard lock | Key lock |
| Size of the safe | Medium |
| Article number | HTDP111 1 |
| Lock against deposit catching | yes |
| Drop system | drawer |
| Adjustable shelves | 1 |
| Anti-burglary protection standard | EN 1143-2 |
| Lacquer/Colour | light grey RAL 7035, structure varnish |
| Lock | high security key lock at the door and the drawer |
| Door opening direction | right side |
| Door opening angle | 180° |
| Door thickness | 130 mm |
| Door clearance dimensions | 456 x 500 mm |
| Protruding door hinges/fittings | 60 mm |
| Features of the lock | - 4-sided bolt locking system, of which additional pins in the hinge area, - emergency bolt locking activated at an attempted break-in |
| Adapted for anchoring in the ground | yes |
| Interior fittings | - 200 mm high drawer on telescopic rails, with armouring and special concrete filling, - max. deposit dimensions: 290*400*20, 220*400*50, 90*400*80 mm |
| More data on the body | 60 mm thick, multi-walled on all sides, complete with high-strength special concrete filling |