

## HTII 200-12

Safe for valuables



### Prime parameters

#### Size of the safe

External dimensions: 1506 mm × 806 mm × 550 mm

#### Resistance class and insurance

Security class II according to EN 1143-1

#### Colour

Choose your safe's standard colour or modify it

#### Key lock

Key lock

# Technical details

External dimensions (H x W x D)	1506 mm x 806 mm x 550 mm
Internal dimensions (H x W x D)	1387 mm x 690 mm x 384 mm
Weight	781 kg
Capacity	367 l
Security class	II
Limit of protected value – home	to 100.000 €
Limit of protected value – company	to 50.000 €
Standard lock	Key lock
Size of the safe	Big
Article number	HTII 200-12
Adjustable shelves	3
File binders	36
Anti-burglary protection standard	EN 1143-1
Certification body	VdS
Fire resistance	LFS 30 P acc. to the EN 15659 standard – 30 min. for paper documents
Door opening direction	right side
Door clearance dimensions	1372 x 672 mm
Door opening angle	180°
Door thickness	109 mm
Protruding door hinges/fittings	60 mm
Lock	high security key lock (2 keys)
Features of the lock	4-sided bolt locking system, among this fixed pins on hinge side
Lacquer/Colour	light grey RAL 7035
Adapted for anchoring in the ground	yes
More data on the body	multi-walled 52 mm, filled with special concrete
Adapted for wall anchoring	no