

## HTII 200-14

Safe for valuables



### Prime parameters

#### Size of the safe

External dimensions: 1806 mm × 806 mm × 550 mm

#### Resistance class and insurance

Security class II according to EN 1143-1

#### Colour

Choose your safe's standard colour or modify it

#### Key lock

Key lock

# Technical details

|                                     |                                                                      |
|-------------------------------------|----------------------------------------------------------------------|
| External dimensions (H x W x D)     | 1806 mm x 806 mm x 550 mm                                            |
| Internal dimensions (H x W x D)     | 1687 mm x 690 mm x 384 mm                                            |
| Weight                              | 910 kg                                                               |
| Capacity                            | 447 l                                                                |
| Security class                      | II                                                                   |
| Limit of protected value – home     | to 100.000 €                                                         |
| Limit of protected value – company  | to 50.000 €                                                          |
| Standard lock                       | Key lock                                                             |
| Size of the safe                    | Big                                                                  |
| Article number                      | HTII 200-14                                                          |
| Adjustable shelves                  | 4                                                                    |
| File binders                        | 42                                                                   |
| Anti-burglary protection standard   | EN 1143-1                                                            |
| Certification body                  | VdS                                                                  |
| Fire resistance                     | LFS 30 P acc. to the EN 15659 standard – 30 min. for paper documents |
| Door opening direction              | right side                                                           |
| Door clearance dimensions           | 1672 x 672 mm                                                        |
| Door opening angle                  | 180°                                                                 |
| Door thickness                      | 109 mm                                                               |
| Protruding door hinges/fittings     | 60 mm                                                                |
| Lock                                | high security key lock (2 keys)                                      |
| Features of the lock                | 4-sided bolt locking system, among this fixed pins on hinge side     |
| Lacquer/Colour                      | light grey RAL 7035                                                  |
| Adapted for anchoring in the ground | yes                                                                  |
| More data on the body               | multi-walled 52 mm, filled with special concrete                     |
| Adapted for wall anchoring          | no                                                                   |