

## HTIII 300-12

Safe for valuables



### Prime parameters

#### Size of the safe

External dimensions: 1506 mm × 836 mm × 700 mm

#### Resistance class and insurance

Security class III according to EN 1143-1

#### Colour

Choose your safe's standard colour or modify it

#### Key lock

Key lock

# Technical details

|                                     |   |
|-------------------------------------|---|
| External dimensions (H x W x D)     | 1506 mm x 836 mm x 700 mm   |
| Internal dimensions (H x W x D)     | 1356 mm x 704 mm x 494 mm   |
| Weight                              | 1067 kg   |
| Capacity                            | 472 l   |
| Security class                      | III   |
| Limit of protected value – home     | to 200.000 €  |
| Limit of protected value – company  | to 100.000 €  |
| Standard lock                       | Key lock  |
| Size of the safe                    | Big   |
| Article number                      | HTIII 300-12  |
| Adjustable shelves                  | 3   |
| File binders                        | 27  |
| Anti-burglary protection standard   | EN 1143-1   |
| Certification body                  | VdS   |
| Fire resistance                     | LFS 30 P acc. to the EN 15659 standard – 30 min. for paper documents  |
| Door opening direction              | right side  |
| Door clearance dimensions           | 1341 x 686 mm   |
| Door opening angle                  | 180°  |
| Door thickness                      | 130 mm  |
| Protruding door hinges/fittings     | 60 mm   |
| Lock                                | high security key lock (2 keys)   |
| Features of the lock                | locking mechanism on four sides, among this fixed pins on hinge side, emergency bolt locking activated at an attempted break-in |
| Lacquer/Colour                      | light grey RAL 7035   |
| Adapted for anchoring in the ground | yes   |
| Adapted for wall anchoring          | no  |
| More data on the body               | 60 mm thick, multi-walled, with a high-strength, special concrete filling   |