HTIII 300-15

Safe for valuables, 2-door



Prime parameters

Size of the safe

External dimensions: 1806 mm × 1200 mm × 700 mm

Resistance class and insurance

Security class III according to EN 1143-1

Colour

Choose your safe's standard colour or modify it

Key lock

Key lock

Technical details

External dimensions (H x W x D)	1806 mm × 1200 mm × 700 mm
Internal dimensions (H x W x D)	1656 mm × 1068 mm × 494 mm
Weight	1641 kg
Capacity	874 l
Security class	III
Limit of protected value – home	to 200.000 €
Limit of protected value – company	to 100.000 €
Standard lock	Key lock
Size of the safe	Big
Article number	HTIII 300-15
Adjustable shelves	4
File binders	56
Anti-burglary protection standard	EN 1143-1
Certification body	VdS
Fire resistance	LFS 30 P acc. to the EN 15659 standard – 30 min. for paper documents
Door opening direction	both sides
Door clearance dimensions	1641 x 1050 mm
Door opening angle	180°
Door thickness	130 mm
Protruding door hinges/fittings	60 mm
Lock	high security key lock (2 keys)
Features of the lock	locking mechanism on all sides, among this fixed pins on hinge side, emergency bolt locking activated at an attempted break-in
Lacquer/Colour	light grey RAL 7035
Adapted for anchoring in the ground	yes
Adapted for wall anchoring	no
More data on the body	60 mm thick, multi-walled, with a high-strength, special concrete filling