# HTIII 300-18

Safe for valuables, 2-door



## Prime parameters

### Size of the safe

External dimensions: 1950 mm × 950 mm × 550 mm

### Resistance class and insurance

Security class III according to EN 1143-1

### Colour

Choose your safe's standard colour or modify it

### Key lock

Key lock

# Technical details

| | |
|---|---|
| External dimensions (H x W x D) | 1950 mm × 950 mm × 550 mm |
| Internal dimensions (H x W x D) | 1800 mm × 818 mm × 344 mm |
| Weight | 1355 kg |
| Capacity | 507 l |
| Security class | III |
| Limit of protected value – home | to 200.000 € |
| Limit of protected value – company | to 100.000 € |
| Standard lock | Key lock |
| Size of the safe | Big |
| Article number | HTIII 300-18 |
| Adjustable shelves | 4 |
| File binders | 55 |
| Anti-burglary protection standard | EN 1143-1 |
| Certification body | VdS |
| Fire resistance | LFS 30 P acc. to the EN 15659 standard – 30 min. for paper documents |
| Door opening direction | both sides |
| Door clearance dimensions | 1785 x 800 mm |
| Door opening angle | 180° |
| Door thickness | 130 mm |
| Protruding door hinges/fittings | 60 mm |
| Lock | high security key lock (2 keys) |
| Features of the lock | locking mechanism on four sides, among this fixed pins on hinge side, emergency bolt locking activated at an attempted break-in |
| Lacquer/Colour | light grey RAL 7035 |
| Adapted for anchoring in the ground | yes |
| Adapted for wall anchoring | no |
| More data on the body | 60 mm thick, multi-walled, with a special concrete filling |