

## HTIV KB 400-04

Safe for valuables



### Prime parameters

#### Size of the safe

External dimensions: 1200 mm × 825 mm × 700 mm

#### Resistance class and insurance

Security class IV KB according to EN 1143-1

#### Colour

Choose your safe's standard colour or modify it

#### Key lock

Key lock

# Technical details

|                                     |   |
|-------------------------------------|---|
| External dimensions (H x W x D)     | 1200 mm x 825 mm x 700 mm   |
| Internal dimensions (H x W x D)     | 1020 mm x 655 mm x 460 mm   |
| Weight                              | 980 kg  |
| Capacity                            | 307 l   |
| Security class                      | IV KB   |
| Limit of protected value – home     | to 400.000 €  |
| Limit of protected value – company  | to 250.000 €  |
| Standard lock                       | Key lock  |
| Size of the safe                    | Big   |
| Article number                      | HTIV KB 400-04  |
| Adjustable shelves                  | 2   |
| File binders                        | 24  |
| Anti-burglary protection standard   | EN 1143-1   |
| Certification body                  | VdS   |
| Door opening direction              | right side  |
| Door opening angle                  | 180°  |
| Protruding door hinges/fitings      | 50 mm   |
| Lacquer/Colour                      | light grey RAL 7035   |
| Lock                                | high security key lock (3 keys included) + mechanical combination lock  |
| Adapted for anchoring in the ground | yes   |
| Features of the lock                | - secured against explosives, - protection against welding and cutting torches in the lock area, - solid, round, steel pins of 40 mm diameter |
| More data on the body               | - three-walled, - ring drill protection, - specially filled and reinforced wall construction  |
| Adapted for wall anchoring          | no  |
| Equipment                           | interior elements in dark grey RAL 7015   |
| More data on the door               | special armoured plating on the locking mechanism   |