

HTS1 041-10

Burglar-proof safe



Prime parameters

Size of the safe

External dimensions: 800 mm × 750 mm × 500 mm

Resistance class and insurance

Security class S1 according to EN 14450

Colour

Choose your safe's standard colour or modify it

Key lock

Key lock

Technical details

External dimensions (H x W x D)	800 mm x 750 mm x 500 mm
Internal dimensions (H x W x D)	794 mm x 732 mm x 435 mm
Weight	99 kg
Capacity	252 l
Security class	S1
Limit of protected value – home	to 5.000 €
Limit of protected value – company	to 2.500 €
Standard lock	Key lock
Size of the safe	Medium
Article number	HTS1 041-10
Adjustable shelves	2
File binders	18
Anti-burglary protection standard	EN 14450
Certification body	VdS
Door opening angle	90°
Door opening direction	right side
Door thickness	52 mm
Door clearance dimensions	710 x 616 mm
Protruding door hinges/fittings	12 mm
Lacquer/Colour	light grey RAL 7035
Features of the lock	4-sided bolt locking system, among this fixed pins on hinge side
Lock	VdS class I key lock (2 keys included)
More data on the body	single-walled, 3mm thick, anchoring required due to high weight of upper part
More data on the door	double-wall with fire safety strip, 6 mm thick plate
Adapted for anchoring in the ground	tak
Adapted for wall anchoring	no