

## HTS1 041-12

Burglar-proof safe



### Prime parameters

#### Size of the safe

External dimensions: 1300 mm × 750 mm × 500 mm

#### Resistance class and insurance

Security class S1 according to EN 14450

#### Colour

Choose your safe's standard colour or modify it

#### Key lock

Key lock

# Technical details

External dimensions (H x W x D)	1300 mm x 750 mm x 500 mm
Internal dimensions (H x W x D)	1294 mm x 732 mm x 435 mm
Weight	148 kg
Capacity	412 l
Security class	S1
Limit of protected value – home	to 5.000 €
Limit of protected value – company	to 2.500 €
Standard lock	Key lock
Size of the safe	Big
Article number	HTS1 041-12
Adjustable shelves	3
File binders	31
Anti-burglary protection standard	EN 14450
Certification body	VdS
Door opening angle	90°
Door opening direction	right side
Door thickness	52 mm
Door clearance dimensions	1210 x 616 mm
Protruding door hinges/ fittings	12 mm
Lacquer/Colour	light grey RAL 7035
Features of the lock	4-sided bolt locking system, among this fixed pins on hinge side
Lock	VdS class I key lock (2 keys included)
More data on the body	single-walled, 3mm thick, anchoring required due to high weight of upper part
More data on the door	double-wall with fire safety strip, 6 mm thick plate
Adapted for anchoring in the ground	tak
Adapted for wall anchoring	no