

HTS1 041-13

Burglar-proof safe



Prime parameters

Size of the safe

External dimensions: 1600 mm × 750 mm × 500 mm

Resistance class and insurance

Security class S1 according to EN 14450

Colour

Choose your safe's standard colour or modify it

Key lock

Key lock

Technical details

| | |
|-------------------------------------|---|
| External dimensions (H x W x D) | 1600 mm x 750 mm x 500 mm |
| Internal dimensions (H x W x D) | 1594 mm x 732 mm x 435 mm |
| Weight | 175 kg |
| Capacity | 508 l |
| Security class | S1 |
| Limit of protected value – home | to 5.000 € |
| Limit of protected value – company | to 2.500 € |
| Standard lock | Key lock |
| Size of the safe | Big |
| Article number | HTS1 041-13 |
| Adjustable shelves | 3 |
| File binders | 38 |
| Anti-burglary protection standard | EN 14450 |
| Certification body | VdS |
| Door opening angle | 90° |
| Door opening direction | right side |
| Door thickness | 52 mm |
| Door clearance dimensions | 1510 x 616 mm |
| Protruding door hinges/fittings | 12 mm |
| Lacquer/Colour | light grey RAL 7035 |
| Features of the lock | 4-sided bolt locking system, among this fixed pins on hinge side |
| Lock | VdS class I key lock (2 keys included) |
| More data on the body | single-walled, 3mm thick, anchoring required due to high weight of upper part |
| More data on the door | double-wall with fire safety strip, 6 mm thick plate |
| Adapted for anchoring in the ground | tak |
| Adapted for wall anchoring | no |