
HTS 115-02

Wall-mounted key safe



Prime parameters

Size of the safe

External dimensions: 550 mm × 500 mm × 200 mm

Resistance class and insurance

Security class S1 according to EN 14450

Colour

Choose your safe's standard colour or modify it

Technical details

External dimensions (H x W x D)	550 mm × 500 mm × 200 mm
Internal dimensions (H x W x D)	544 mm × 494 mm × 123 mm
Weight	37 kg
Capacity	38 l
Security class	S1
Limit of protected value – home	to 5.000 €
Limit of protected value – company	to 2.500 €
Size of the safe	Small
Article number	HTS 115-02
Key hooks	150
Adjustable hook slats	no
Door opening direction	right side
Door thickness	57 mm
Door opening angle	180°
Door clearance dimensions	488 x 438 mm
Protruding door hinges/fittings	12 mm
Lacquer/Colour	light grey RAL 7035
Lock	VdS class I key lock (2 keys)
Features of the lock	3-sided bolt locking system; in addition, fixed pins to protect the hinge area
More data on the body	single-walled, 3 mm thick, wrap around fire safety strip
More data on the door	double-walled, 6 mm thick plate
Adapted for anchoring in the ground	yes
Adapted for wall anchoring	yes
Equipment	- pre-installed for up to 150 hooks (additional equipment), - hooks available in lengths of 20, 30 and 40 mm depending on the size and width of the keys and bunches, - key list holder