

## HTS 116-01

Key safe



### Prime parameters

#### Size of the safe

External dimensions: 350 mm × 350 mm × 200 mm

#### Resistance class and insurance

Security class S1 according to EN 14450

#### Colour

Choose your safe's standard colour or modify it

#### Key lock

Key lock

# Technical details

External dimensions (H x W x D)	350 mm x 350 mm x 200 mm
Internal dimensions (H x W x D)	344 mm x 344 mm x 125 mm
Weight	18 kg
Capacity	17 l
Security class	S1
Limit of protected value – home	to 5.000 €
Limit of protected value – company	to 2.500 €
Standard lock	Key lock
Size of the safe	Small
Article number	HTS 116-01
Key hooks	50
Adjustable hook slats	no
Door opening direction	right side
Door thickness	52 mm
Door opening angle	90°
Door clearance dimensions	260 x 213 mm
Protruding door hinges/fitings	12 mm
Lacquer/Colour	light grey RAL 7035
Lock	key lock (2 keys)
Features of the lock	3-sided bolt locking system; in addition, fixed pins to protect the hinge area
More data on the body	3 mm thick, wrap around fire safety strip
More data on the door	6 mm thick plate
Adapted for anchoring in the ground	yes
Adapted for wall anchoring	yes
Equipment	- pre-installed for up to 50 hooks (additional equipment), - key hooks at the rear wall, door and side walls can be freely adjusted vertically and horizontally, - the hook lengths of your choice