

HTS 116-02

Key safe



Prime parameters

Size of the safe

External dimensions: 550 mm × 500 mm × 200 mm

Resistance class and insurance

Security class S1 according to EN 14450

Colour

Choose your safe's standard colour or modify it

Key lock

Key lock

Technical details

| | |
|-------------------------------------|---|
| External dimensions (H x W x D) | 550 mm x 500 mm x 200 mm |
| Internal dimensions (H x W x D) | 544 mm x 494 mm x 125 mm |
| Weight | 37 kg |
| Capacity | 39 l |
| Security class | S1 |
| Limit of protected value – home | to 5.000 € |
| Limit of protected value – company | to 2.500 € |
| Standard lock | Key lock |
| Size of the safe | Small |
| Article number | HTS 116-02 |
| Key hooks | 150 |
| Adjustable hook slats | no |
| Door opening direction | right side |
| Door thickness | 52 mm |
| Door opening angle | 90° |
| Door clearance dimensions | 460 x 363 mm |
| Protruding door hinges/fitings | 12 mm |
| Lacquer/Colour | light grey RAL 7035 |
| Lock | key lock (2 keys) |
| Features of the lock | 3-sided bolt locking system; in addition, fixed pins to protect the hinge area |
| More data on the body | 3 mm thick, wrap around fire safety strip |
| More data on the door | 6 mm thick plate |
| Adapted for anchoring in the ground | yes |
| Adapted for wall anchoring | yes |
| Equipment | - pre-installed for up to 150 hooks (additional equipment), - key hooks at the rear wall, door and side walls can be freely adjusted vertically and horizontally, - the hook lengths of your choice |