HTS 116-02

Key safe



Prime parameters

Size of the safe

External dimensions: 550 mm × 500 mm × 200 mm

Resistance class and insurance

Security class S1 according to EN 14450

Colour

Choose your safe's standard colour or modify it

Key lock

Key lock

Technical details

External dimensions (H x W x D)	550 mm × 500 mm × 200 mm
Internal dimensions (H x W x D)	544 mm × 494 mm × 125 mm
Weight	37 kg
Capacity	39 l
Security class	S1
Limit of protected value – home	to 5.000 €
Limit of protected value – company	to 2.500 €
Standard lock	Key lock
Size of the safe	Small
Article number	HTS 116-02
Key hooks	150
Adjustable hook slats	no
Door opening direction	right side
Door thickness	52 mm
Door opening angle	90°
Door clearance dimensions	460 x 363 mm
Protruding door hinges/fittings	12 mm
Lacquer/Colour	light grey RAL 7035
Lock	key lock (2 keys)
Features of the lock	3-sided bolt locking system; in addition, fixed pins to protect the hinge area
More data on the body	3 mm thick, wrap around fire safety strip
More data on the door	6 mm thick plate
Adapted for anchoring in the ground	yes
Adapted for wall anchoring	yes
Equipment	- pre-installed for up to 150 hooks (additional equipment), - key hooks at the rear wall, door and side walls can be freely adjusted vertically and horizontally, - the hook lengths of your choice