

HTS 119-03

Wall-mounted key safe



Prime parameters

Size of the safe

External dimensions: 806 mm × 520 mm × 250 mm

Resistance class and insurance

Security class S2 according to EN 14450

Colour

Choose your safe's standard colour or modify it

Key lock

Key lock

Technical details

| | |
|-------------------------------------|---|
| External dimensions (H x W x D) | 806 mm x 520 mm x 250 mm |
| Internal dimensions (H x W x D) | 686 mm x 400 mm x 110 mm |
| Weight | 72 kg |
| Capacity | 36 l |
| Security class | S2 |
| Limit of protected value – home | to 30.000 € |
| Limit of protected value – company | to 2.500 € |
| Standard lock | Key lock |
| Size of the safe | Medium |
| Article number | HTS 119-03 |
| Key hooks | 150 |
| Adjustable hook slats | yes |
| Door opening direction | right side |
| Door thickness | 60 mm |
| Door opening angle | 180° |
| Door clearance dimensions | 658 x 372 mm |
| Protruding door hinges/fitings | 12 mm |
| Lacquer/Colour | light grey RAL 7035 |
| Lock | key lock (2 keys) |
| Features of the lock | 3-sided bolt locking system; in addition, fixed pins to protect the hinge area |
| More data on the body | double-wall, 60 mm thick, wrap around fire safety strip |
| More data on the door | double-walled, 6 mm thick plate |
| Adapted for anchoring in the ground | yes |
| Adapted for wall anchoring | yes |
| Equipment | - 15 adjustable hook rails, coloured and numbered, 10 hooks per rail, - key list holder |