

## HTS 119-04

Wall-mounted key safe



### Prime parameters

#### Size of the safe

External dimensions: 1200 mm × 670 mm × 300 mm

#### Resistance class and insurance

Security class S2 according to EN 14450

#### Colour

Choose your safe's standard colour or modify it

#### Key lock

Key lock

# Technical details

External dimensions (H x W x D)	1200 mm x 670 mm x 300 mm
Internal dimensions (H x W x D)	1080 mm x 550 mm x 160 mm
Weight	105 kg
Capacity	107 l
Security class	S2
Limit of protected value – home	to 30.000 €
Limit of protected value – company	to 2.500 €
Standard lock	Key lock
Size of the safe	Big
Article number	HTS 119-04
Key hooks	300
Adjustable hook slats	yes
Door opening direction	right side
Door thickness	60 mm
Door opening angle	180°
Door clearance dimensions	1052 x 522 mm
Protruding door hinges/fitings	12 mm
Lacquer/Colour	light grey RAL 7035
Lock	key lock (2 keys)
Features of the lock	3-sided bolt locking system; in addition, fixed pins to protect the hinge area
More data on the body	double-wall, 60 mm thick, wrap around fire safety strip
More data on the door	double-walled, 6 mm thick plate
Adapted for anchoring in the ground	yes
Adapted for wall anchoring	yes
Equipment	- 20 adjustable hook rails, coloured and numbered, 15 hooks per rail, - key list holder