

HTS 119-06

Wall-mounted key safe



Prime parameters

Size of the safe

External dimensions: 1800 mm × 670 mm × 300 mm

Resistance class and insurance

Security class S2 according to EN 14450

Colour

Choose your safe's standard colour or modify it

Key lock

Key lock

Technical details

External dimensions (H x W x D)	1800 mm x 670 mm x 300 mm
Internal dimensions (H x W x D)	1680 mm x 550 mm x 160 mm
Weight	152 kg
Capacity	166 l
Security class	S2
Limit of protected value – home	to 30.000 €
Limit of protected value – company	to 2.500 €
Standard lock	Key lock
Size of the safe	Big
Article number	HTS 119-06
Key hooks	510
Adjustable hook slats	yes
Door opening direction	right side
Door thickness	60 mm
Door opening angle	180°
Door clearance dimensions	1352 x 522 mm
Protruding door hinges/fitings	12 mm
Lacquer/Colour	light grey RAL 7035
Lock	key lock (2 keys)
Features of the lock	3-sided bolt locking system; in addition, fixed pins to protect the hinge area
More data on the body	double-wall, 60 mm thick, wrap around fire safety strip
More data on the door	double-walled, 6 mm thick plate
Adapted for anchoring in the ground	yes
Adapted for wall anchoring	yes
Equipment	- 34 adjustable hook rails, coloured and numbered, 15 hooks per rail, - key list holder