

## HTS 120-01

Key safe



### Prime parameters

#### Size of the safe

External dimensions: 600 mm × 500 mm × 500 mm

#### Resistance class and insurance

Security class S2 according to EN 14450

#### Colour

Choose your safe's standard colour or modify it

#### Key lock

Key lock

# Technical details

External dimensions (H x W x D)	600 mm x 500 mm x 500 mm
Internal dimensions (H x W x D)	480 mm x 380 mm x 355 mm
Weight	200 kg
Capacity	66 l
Security class	S2
Limit of protected value – home	to 30.000 €
Limit of protected value – company	to 2.500 €
Standard lock	Key lock
Size of the safe	Small
Article number	HTS 120-01
Key hooks	320
Adjustable hook slats	yes
Door opening direction	right side
Door thickness	78 mm
Door opening angle	180°
Door clearance dimensions	480 x 380 mm
Protruding door hinges/fitings	12 mm
Lacquer/Colour	light grey RAL 7035
Lock	key lock (2 keys)
Features of the lock	3-sided bolt locking system; in addition, fixed pins to protect the hinge area
More data on the body	double-wall, 60 mm thick, wrap around fire safety strip
More data on the door	double-walled
Adapted for anchoring in the ground	yes
Adapted for wall anchoring	yes
Equipment	- 4 pull-out boards, 8 rails with 10 key hooks each, - hook rails: coloured, not numbered, vertically adjustable