

HTS 120-05

Key safe



Prime parameters

Size of the safe

External dimensions: 1000 mm × 636 mm × 500 mm

Resistance class and insurance

Security class S2 according to EN 14450

Colour

Choose your safe's standard colour or modify it

Key lock

Key lock

Technical details

External dimensions (H x W x D)	1000 mm x 636 mm x 500 mm
Internal dimensions (H x W x D)	880 mm x 516 mm x 355 mm
Weight	300 kg
Capacity	164 l
Security class	S2
Limit of protected value – home	to 30.000 €
Limit of protected value – company	to 2.500 €
Standard lock	Key lock
Size of the safe	Medium
Article number	HTS 120-05
Key hooks	1400
Adjustable hook slats	yes
Door opening direction	right side
Door thickness	78 mm
Door opening angle	180°
Door clearance dimensions	880 x 516 mm
Protruding door hinges/fitings	12 mm
Lacquer/Colour	light grey RAL 7035
Lock	key lock (2 keys)
Features of the lock	3-sided bolt locking system; in addition, fixed pins to protect the hinge area
More data on the body	double-wall, 60 mm thick, wrap around fire safety strip
More data on the door	double-walled
Adapted for anchoring in the ground	yes
Adapted for wall anchoring	yes
Equipment	- 7 pull-out boards, 20 rails with 10 key hooks each, - hook rails: coloured, not numbered, vertically adjustable