

HTS 121-07

Key safe



Prime parameters

Size of the safe

External dimensions: 1236 mm × 736 mm × 500 mm

Resistance class and insurance

Security class I according to EN 1143-1

Colour

Choose your safe's standard colour or modify it

Key lock

Key lock

Technical details

External dimensions (H x W x D)	1236 mm x 736 mm x 500 mm
Internal dimensions (H x W x D)	1145 mm x 664 mm x 381 mm
Weight	390 kg
Capacity	287 l
Security class	I
Limit of protected value – home	to 65.000 €
Limit of protected value – company	to 20.000 €
Standard lock	Key lock
Size of the safe	Big
Article number	HTS 121-07
Key hooks	1950
Adjustable hook slats	yes
Door opening direction	right side
Door thickness	84 mm
Door opening angle	90°
Door clearance dimensions	1130 x 594 mm
Lacquer/Colour	light grey RAL 7035
Lock	key lock (2 keys)
Features of the lock	4-sided bolt locking system, additional security by inner hinges
More data on the body	double-wall, 38 mm thick, wrap around fire safety strip
More data on the door	multi-walled, 12 mm thick plate
Adapted for anchoring in the ground	yes
Adapted for wall anchoring	no
Equipment	- 8 pull-out boards, 195 rails with 10 key hooks each, - hook rails: coloured, not numbered, vertically adjustable