# HTS 121-07

Key safe



## Prime parameters

### Size of the safe

External dimensions: 1236 mm × 736 mm × 500 mm

### Resistance class and insurance

Security class I according to EN 1143-1

### Colour

Choose your safe's standard colour or modify it

### Key lock

Key lock

# Technical details

| | |
|---|---|
| External dimensions (H x W x D) | 1236 mm × 736 mm × 500 mm |
| Internal dimensions (H x W x D) | 1145 mm × 664 mm × 381 mm |
| Weight | 390 kg |
| Capacity | 287 l |
| Security class | I |
| Limit of protected value – home | to 65.000 € |
| Limit of protected value – company | to 20.000 € |
| Standard lock | Key lock |
| Size of the safe | Big |
| Article number | HTS 121-07 |
| Key hooks | 1950 |
| Adjustable hook slats | yes |
| Door opening direction | right side |
| Door thickness | 84 mm |
| Door opening angle | 90° |
| Door clearance dimensions | 1130 x 594 mm |
| Lacquer/Colour | light grey RAL 7035 |
| Lock | key lock (2 keys) |
| Features of the lock | 4-sided bolt locking system, additional security by inner hinges |
| More data on the body | double-wall, 38 mm thick, wrap around fire safety strip |
| More data on the door | multi-walled, 12 mm thick plate |
| Adapted for anchoring in the ground | yes |
| Adapted for wall anchoring | no |
| Equipment | - 8 pull-out boards, 195 rails with 10 key hooks each, - hook rails: coloured, not numbered, vertically adjustable |