

HTS 320-06

Key management system

6				
219	2	230	60	\$ 5 P
969	079	900	90	10 g
9 11 9	12	9 13 9	9149	G 15 9
9 16 9	9 17 9	9 18 9	G 19 9	G 20 9
21	22	23	@ 24 O	G25 0
26	27	S 28	C 29	C 30 0
31	32	S 33	Q 34 Q	C 35 0
36	37	38	(C 39 (C)	C 40 9
9 41 9	9 42 9	6 43 0	Q 44 Q	C ⁴⁵ 9
46 0	47 9	9 48 9	Q 49 Q	C2 50 C
O 51 O	52 9	53 0	Q 54 Q	C 55
56 9	57 9	58	C 59 C	60 60
61	62 9	€ 63 C	664	C 65 C
66 9	67 9	68	69 69	C 70
0 71 9	O 72	73	A 74	C 75
76	0 77 9	78	(19 S	C 80 C
81 0	82 9	83	A 84 9	C.S.C
86	87	88	(3 ⁸⁹)	10 ⁹⁰
91 9	92	93	8 94 C	(1 ⁹⁵)
96 9	97	1 98 98	(99 (P	100 C

Prime parameters

Size of the safe

External dimensions: 865 mm × 552 mm × 80 mm

Colour

Choose your safe's standard colour or modify it

Key lock

Key lock

HARTMANN TRESORE Polska Sp. z o. o tel. +48 22 850 40 45 www.hartmann-tresore.pl

Technical details

External dimensions (H x W x D)	865 mm × 552 mm × 80 mm		
Internal dimensions (H x W x D)	mm × mm × mm		
Weight	12 kg		
Standard lock	Key lock		
Size of the safe	Medium		
Article number	HTS 320-06		
Key hooks	100		
Lock	high security key lock (3 keys) and mechanical combination lock		
Features of the lock	- secured against explosives, - lock area protected against welding and torch cutting, - solid, round, steel locking bolts measuring 40 mm, - special armoured plating on the locking mechanism		
Adapted for anchoring in the ground	no		
Adapted for wall anchoring	yes		
Equipment	- modular construction, without a rack, - mechanical control and management system for 100 keys, - 20 rows of 5 slots numbered from 1–100, including 100 key pins and security seals		

HARTMANN TRESORE Polska Sp. z o. o tel. +48 22 850 40 45 www.hartmann-tresore.pl